



Key Switches



CM1000

- Heavy duty weather resistant 1-piece die cast surface box with 1/4" thick aluminum plate
- Supplied with rubber gasket.
- Accepts standard mortise cylinders from 1" to 1 1/4" (not supplied)
- Tamper proof screws provided
- UL/CSA Single pole single throw momentary normally open switch supplied rated at 6A/120VAC & 3A/250VAC
- Size: 4-1/2"H x 2-3/4"W x 2"D
- For indoor or outdoor applications



CM2000

- Similar to CM1000 but for narrow stile applications. Does not include backbox.
- Supplied with rubber gasket.
- Accepts standard mortise cylinders from 1" to 1 1/4" (not supplied)
- Tamper proof screws provided
- UL/CSA Single pole single throw momentary normally open switch supplied rated at 6A/120VAC & 3A/250VAC
- Size: 4-1/2"H x 1-3/4"W x 1-1/2"D
- For indoor or outdoor applications

Mfg #	Description	EZ #
CM1000	Gang Mount Switch Box	036125
CM2000	Narrow Stile Switch	080388
CM1000/30	Replacement Switch for CM1000 & CM2000	036124

Handicap Operator Pushbutton Switches



CM25 2



CM250 2



CM280 2



CM45 2



CM60 2

- Durable stainless steel construction with tamper resistant fastening on all active units due to small holes in front of plate.

Application

- CM25 2, CM250 2: Mounts in aluminum jamb or in surface boxes
- CM45 2: Mounts in a single or double gang box.
- CM60 2: Mounts in a single or double gang, and 4" x 4" box (with included adapter plate)
- CM280 2: Mounts in a single gang box

Actuation

- CM25 2, CM45 2, CM60 2: All-active design requires minimal actuation force & meets handicap requirements as well as withstanding high traffic.
- CM250 2, CM280 2: 1" Red button requires minimal actuation force and meets handicap requirements

Switch Specification

- CM25 2: UL/CSA approved SPST N.O. switch rated 3 amps @ 120VAC.
- CM250 2, CM280 2, CM45 2, CM60 2: UL/CSA approved SPDT N.O. switch rated 15Amp @ 125VAC.

Mfg #	Type	Size	EZ #
CM25 2	All Active	1-5/8"W x 4-1/2"H	081813
CM250 2	Standard	1-5/8"W x 4-1/2"H	081816
CM280 2	Standard	2-3/4"W x 4-1/2"H	081817
CM45 2	All Active	4-1/2" x 4-1/2"	081814
CM60 2	All Active	6" Diameter	081815



CM701BE

Pull Station

- Single gang mount
- Switch: 1amp @ 30VDC or 25A @125VAC
- Often required by code when installing an electromagnetic lock.
- Versions stocked (not shown) has French & English on label.

Mfg #	EZ #
CM701BE	086878

Door Sequencing Board



SA1 [INDC]

- Ideal for (de)energizing electric strikes or electromagnet and after set time activating an automatic door operator
- Can be used for timing functions such as door sequencing in one direction.
- 3 Adjustable delays, from .5 to 30 seconds using easy potentiometer adjustment
- LED's for visual relay confirmation
- Accepts wet or dry inputs
- Latching mode toggles output #2 only, or outputs #1 & #2
- Separate momentary and extended trigger inputs for increased functionality
- SPDT contacts rated at 2 amps @ 28VDC
- Input power of 12 to 24 VAC/DC
- Dip switch change converts operation for a maintained input and output
- Noise filtering on the triggers to protect against false triggering

Mfg #	EZ #
SA1 [INDC]	080734

Stand Alone Proximity Reader System



CV600

- Up to 99 users
- Vandal and water resistant jamb mounted proximity reader.
- Reader & controller can be on other side of door or up to 200' apart.
- Operates with HID prox cards or Fobs which can be individually or batch enrolled or deleted.
- Request to Exit Input
- Door open time can set from between 1-180 seconds
- 1 Form C (NO & NC) 5 Amp @12VAC or 30VDC relay
- Can be powered by 12/24V AC or DC
- Includes presence detector input

Mfg #	EZ #
CV600	Available by Special Order

Heavy Duty Armoured Power Transfer Cable



CMPTSS18

Mfg #	EZ #
CMPTSS18	085280

- Not exactly as pictures. Unit stocked has stainless steel end caps and are in a slightly different configuration..
- Stainless steel cable with 1/4" inside diameter

7 Day Timer



CX247

- Programmable 7 day timer with 8 daily & weekly schedules.
- Memory backup in case of a power loss
- Water resistant enclosure
- Size: 2-3/8" L x 2-3/8" W x 1/14" D
- Current Draw: .1 mA Idle, 10 mA Operating
- 1 SPDT Relay
- Contact Rating 16 Amps @277VAC/30VDC

Mfg #	Voltage	EZ #
CX247 12	12VAC/DC	075472
CX247 24	24VAC/DC	075473