

Camtek Network MPEG 4 Digital Video Recorder (DVR)

CAMTEK

Camtek



DVR-466



DVR-866

All Sold Less Hard Disk



DVR-166

DVR-466 4 Channel DVR

- Embedded LINUX operating system.
- Triplex Function: Records, Local Playback, & Network Viewing at the same time.
- Compression Method: MPEG 4
- Operating Temperature: 5°C to 40°C with Humidity Less Than 90%
- Backup Methods: Included CD-RW, USB 2.0., TCP-IP Network
- TCP-IP Microsoft Internet Explorer Browser Functions: Live View, Playback, Recording, Administrative Control
- Network Input: RJ45
- RCA Audio: 4 Channels In, 1 Out
- Alarm Outputs: 4 In, 1 Form C Relay Out, Normally Open & Normally Closed
- Alarm Trigger Relay: Alarm, Motion, Video Loss
- Average Video Stream: .5Mbps to 3Mbps
- BNC Inputs: 4
- BNC Outputs: 4 Video looping out, Monitor
- S-Video Output: 1
- NTSC Pixel Resolution: 720H x 480V
- 1/4 Split Screen Resolution: 360H x 240V
- Colours: 16.7 Million
- Display Rate Live: 120fps
- Display Monitoring: Split Screen, 1, 4, 9, Picture-in-Picture, Channel Sequence
- Digital Zoom Live: 2 x 2
- Recording : 120FPS
- Recording NTSC Field : Full, Half, 20, 10, 4
- Recording NTSC CIF: Full, Half, 40, 20, 8
- Record Quality Modes: Super, High, Fine, Normal, Low
- Selectable Recording Modes: Normal, Times Schedule, Motion Detection, Alarm Input

- Playback Mode by: Date & Time search or by Event search
- Motion Detection Area Division: 16 x 12, On/Off Sector Selectable.
- RS485 Control: For Keyboard Control or PTZ Zoom
- Storage 4 IDE HDD, Up to 500 Gigabytes Total
- Included Infrared Remote Controller Standard
- Power Supply: Included 12VDC @ 5A
- Dimensions: 17.33W x 15.83D x 3.47H

DVR-866 8 Channel DVR

Like DVR-466 but with following differences:

- BNC Inputs: 8
- BNC Outputs: 8 Video looping out, Monitor
- Display Rate Live: 240fps
- Alarm Outputs: 8 In, 4 Form C Relay Out, Normally Open & Normally Closed
- Record Quality Modes: Super, Fine, Low
- Mouse Control

DVR-166 16 Channel DVR

Like DVR-866 but with following differences.

- BNC Inputs: 16
- BNC Outputs: 16 Video looping out, Monitor
- Display Rate Live: 480fps
- Alarm Outputs: 16 In, 4 Form C Relay Out, Normally Open & Normally Closed
- Dimensions: 16.78W x 12.91D x 2.56H

| Mfg # | Channels | EZ # |
|---------|----------|--------|
| DVR-466 | 4 | 088385 |
| DVR-866 | 8 | 088386 |
| DVR-166 | 16 | 088387 |