

One Hour Fire & Burglary Safes



Gardall



FB1212GE



FB2013GE



FB2714GE

- Heavy duty construction 2" thick door, 3" thick body
- Composite construction door & body
- Independent glass re-locking system
- 3 Spoke chrome plated vault handle

- 1 Hour U.L. 350° fire label
- U.L. RSC Burglary Label
- Center bolt down for ease of installation (hardware included)

- 1-1/4" Chrome plated locking bolts
- Attractive two tone paint for increased durability
- U.L. Group II combination or electronic (S&G) lock standard

Mfg#	Lock Type	Outside H x W x D	Inside H x W x D	Cubic Inches	Lbs	Shelves	EZ #
FB1212GE	Electronic	17-3/4" x 17-3/4" x 20-1/2"	12" x 12" x 12-3/4"	1836	205	1	086809
FB1212GC	Mechanical	17-3/4" x 17-3/4" x 20-1/2"	12" x 12" x 12-3/4"	1836	205	1	075010
FB2013GE	Electronic	27" x 20" x 20-1/2"	21-1/4" x 14-1/4" x 13"	3523	312	2	086810
FB2013GC	Mechanical	27" x 20" x 20-1/2"	21-1/4" x 14-1/4" x 13"	3523	312	2	075011
FB2714GE	Electronic	33-1/2" x 20" x 22-3/4"	27-1/2" x 14-1/8" x 15-1/4"	5982	412	2	086811
FB2714GC	Mechanical	33-1/2" x 20" x 22-3/4"	27-1/2" x 14-1/8" x 15-1/4"	5982	412	2	086880

Microwave Style Fire Safes



MS911GCK

MS911GE

- Available with standard mechanical lock or programmable electronic lock with over-ride code.
- One-hour fire safe (Non UL)
- Securely packaged for courier shipping.
- Powder coated paint for increased durability.
- Pull-out shelf for storage.
- Center hole bolt down hardware kit included.
- Dual custody key and combination (mechanical only)
- Outside Dimensions: 11-1/2"H x 15-1/4"W x 12-1/2"D
- Inside Dimensions: 8-1/2"H x 12" W x 8-1/2"D
- Weight: 61 lbs.

Mfg#	Lock Type	EZ #
MS911GE	Electronic	082782
MS911GCK	Mechanical	074477



Two Hour Record Safes



SS 2517GCK



ES 1612GE

- Passed KIS Fire Test which has an extreme furnace temperature up to 1832°F for two hours. The interior of the safe was not damaged and only rose to 232°F; more than 200°F below the charring point of paper.
- For residential or commercial use.
- Available with an attractive two-tone glossy finish.
- 1 Shelf & 1 tray
- **ES1612GE & SS1612GCK**
- Tested and listed for U.L. 350° One-Hour Label – Fire and Impact Test **SS2517GCK**
- S&G Group II combo lock
- 3 Way bolt work (5 active bolts)
- Day lock
- Pull out inner key locking compartment
- Center hole bolt down hardware kit included.

Mfg#	Lock Type	Outside H x W x D	Inside H x W x D	Lbs	EZ #
ES1612GE	Electronic	20" x 16-1/4" x 17-1/2"	14-1/2" x 12" x 14-3/8"	140	086806
SS1612GCK	Mechanical	20" x 16-1/4" x 17-1/2"	14-1/2" x 12" x 14-3/8"	140	086805
SS2517GCK	Mechanical	31-3/4" x 23-1/4" x 25"	24-3/4" x 16-1/3" x 13-1/4"	352	086807



DS 1914GC

Front Load Depository Safe

- "B" rated solid 1/2" thick steel door 1/4" body
- 3 Way locking bolts
- Anchoring holes for ease of installation
- Anti fish baffles
- Electronic welding for strength
- UL Group II combination lock (S&G)
- Powder coated paint for durability
- External re-locker
- Excellent for mounting in delivery vehicles
- Mounting holes pre-drilled
- Laser cut door for exact fit

Mfg#	Outside H x W x D	Inside H x W x D	Lbs	EZ #
DS1914GC	19" x 13-1/2" x 15"	12" x 12-3/4" x 12"	128	082784