

GLYNN-JOHNSON 

Heavy Duty Door Holders

Glynn-Johnson & Ives



| Mfg # | Type | Size | Door Opening Butts | Door Opening Center Hung | Type | EZ # |
|---------|-----------|------|--------------------|--------------------------|-----------|--------|
| 104S630 | Stop Only | 4 | 33-1/16" - 39" | 45-1/16" - 51" | Concealed | 085716 |
| 903S630 | Stop Only | 3 | 27-1/16" - 33" | 33-1/16" - 39" | Surface | 076442 |
| 904H32D | Hold Open | 4 | 33-1/16" - 39" | 39-1/16" - 45" | Surface | 074587 |
| 904S32D | Stop Only | 4 | 33-1/16" - 39" | 39-1/16" - 45" | Surface | 070298 |

- For heavy-duty applications these door holders are non-handed.
- 900 Series: Channel is surface-mounted to the door, most often with sex bolts, and the jamb bracket is surface mounted to the jamb, requiring minimal door and frame preparation.
- Can be used in conjunction with most surface-applied door closers.
- Can be mounted for openings ranging from 85° to 110°
- **Hold-Open Function**
 - Holds the door open at a pre-determined position permitting an unobstructed traffic flow through the opening.
 - Can easily be turned on or off by simply rotating the serrated knob on the bottom of the channel to engage the hold open mechanism. When flipped over it acts as a stop and shock absorber.
 - Tension on the Hold-Open mechanism can be adjusted to offset air currents or other exterior conditions.
- **Stop Function**
 - Provides a reliable method for shock absorbing capability
 - Can be used on fire doors.

Door Stop & Bolts



FS544

- Floor to Door Clearance: 2" or less
- Plate Height: 2-1/4"
- Plate Width: 1-7/16"
- Cast of durable iron.
- Rubber shoes provide secure grip,

(Bottom Strike)



SB1630 (Top Strike)

- Standard surface bolt has 1" throw
- Available in locking version.
- Constructed of heavy duty steel.



- UL listed up to 3 hours when used on the inactive door of pair up to 8' in height.
- Meets ANSI/BHMA A156.16, L84161.

- Constant Latching - inactive door remains latched until the active door is opened, releasing the automatic bottom bolt and then the top bolt can be manually released.
- Inactive door will re-latch automatically when closed.
- Low Actuation Forces.
- Bolts have 3/4" throw with a 7/8" vertical adjustment.
- Standard Rod Length is 12", which is measured from the center of the flush bolt body to the bolt tip.

FB51P

- Door & Frame Preparation: ANSI A115.4
- Non-handed.
- Body Size: 1" W x 6-3/4" L x 2" Deep
- Guide Size: 1" W x 1-27/32" L x 11/16" H x 3/32" T (Top)
- Guide Size: 1" W x 1-27/32" L x 27/32" H x 3/32" T (Bottom)
- Strike Size: 15/16" W x 2-1/4" L x 1/16" T
- Rub Plate Size: 1-1/4" W x 1-11/16" L x 3/64" T
- Filler Plate Size: 1" W x 6-3/4" L x 3/32" T

| Mfg # | Description | EZ # |
|---------------|-------------------------------|--------|
| FB51P630 | Flush Bolt Set | 091025 |
| FS544 4" SP28 | Kick Down Door Stop | 035841 |
| 4 6 | Replacement Heel for FS544 | 035835 |
| SB1630B US2G | Bottom Surface Bolt | 035837 |
| SB1630BL US2G | Bottom Surface Bolt (Locking) | 035838 |
| SB1630T US2G | Top Surface Bolt | 035839 |
| SB1630TL US2G | Top Surface Bolt (Locking) | 035840 |

Roller Latch



RL30A

| Mfg # | EZ # |
|----------|--------|
| RL30A626 | 035554 |

- Closing of the door causes the nylon roller to fall in the depression of the strike, thereby holding the door closed.
- Projection of roller is easily adjusted.
- Maximum projection of the roller is 3/8"
- Forged Brass Construction.
- Body Size: 1" Wide x 3-3/8" L x 1-11/16" D
- ASA Strike: 1-1/4" Wide x 4-7/8" Long x 5/32" Thick