

## McKINNEY Single Acting Spring Hinge



**1502**

Mfg #	EZ #
1502 26D	072883

- Non handed hinge series has infinite adjustments with the tension being added or reduced by means of provided hex key.
- Locking screw provides tamper-resistance after the proper tension has been set.
- Nylon tee bearings for vertical and lateral loads.
- Coil spring provides closing power.
- Steel base material polished and plated.
- Size: 4-1/2" x 4"

## Standard Duty Ball Bearing



**TA2714**

Mfg #	Description	Base	EZ #
TA2714 26D	Standard	Steel	072878
TA2714NRP 26D	NRP	Steel	072879
TA2314NRP26D4.5X4	NRP	Brass or Bronze	075302

- Steel base (TA2714) or brass or bronze (TA2314) polished and plated
- Recommended for standard weight, medium frequency doors, or doors with closing devices.
- Size 4-1/2" x 4"
- NRP: Non removable pin prevents removal of hinge pin when door closed.

## Plain Bearing Hinges



**MACPRO**

- Plain bearing hinge.
- Steel base material polished and plated



**T2714**

- Recommended for standard weight doors without closing devices.
- Size 4-1/2" x 4"

Mfg #	Finish	EZ #
MACPRO4.5X4 26D	Brushed Chrome	084874
T2714 26D	Brushed Chrome	072877

## Concealed Wire Hinges



**TA2714CC4  
TA2714CC8**

- Stocked with 2 or 4 circuits of 2 wires 28AWG stranded wire with 12" leads.
- 4 Amp, 24 Volts maximum each circuit continuous duty, 16.0 Amps intermittent duty (pulse) for 300 milliseconds.
- Electric feature undetectable when hinge is installed
- ULC Listed

Mfg #	Wires	EZ #
TA2714CC4 4.5X4 26D	4	072882
TA2714CC8 4.5X4 26D	8	101403

## Plain Bearing Half Mortise



**T2772P**

- Recommended for use on minimum frequency and/or light weight wood or stock hollow metal doors in residences, apartments or other very low frequency doors in commercial construction.
- Finish: Prime
- Size: 4-1/2" x 4"

Mfg #	EZ #
T2772P	080387

## Full Mortise Heavy Duty



**T4A3386**

- Stainless steel base polished and brushed chrome plated.
- Recommended for use on high frequency and/or heavy wood or metal doors in schools, hospitals or other public buildings where heavy traffic is experienced.
- Stocked 4-1/2" x 4-1/2" with NRP non removable pin feature

Mfg #	EZ #
T4A3386 NRP 26D	072881